









Triac Products

+ Evolving green innovation and future



* I * for insulated



	TO-92	TO-251	TO-252	TO-263	TO-220AB	TO-3P	TO-3
							
	1A	4A,6A,8A	4A,6A,8A	8A,10A,12A,16A 20A,25A	4A,6A,8A,10A,12A 16A,20A,25A	20A,25A,40A	40A,55A
600V	1T06E	4T06F 6T06F 8T06F	4T06G 6T06G 8T06G	8T06H 10T06H 12T06H 16T06H 20T06H 25T06H	4T06A(I) 6T06A(I) 8T06A(I) 10T06A(I) 12T06A(I) 16T06A(I) 20T06A(I) 25T06A(I)	20T06B(I) 26T06B(I) 41T06B(I)	M40T60A M55T60A
800V	1T08E	4T08F 6T08F 8T08F	4T08G 6T08G 8T08G	8T08H 10T08H 12T08H 16T08H 20T08H 25T08H	4T08A(I) 6T08A(I) 8T08A(I) 10T08A(I) 12T08A(I) 16T08A(I) 20T08A(I) 25T08A(I)	20T08B(I) 26T08B(I) 41T08B(I)	M40T80A M55T80A
1000V		4T10F 6T10F 8T10F	4T10G 6T10G 8T10G	8T10H 10T10H 12T10H 16T10H 20T10H 25T10H	4T10A(I) 6T10A(I) 8T10A(I) 10T10A(I) 12T10A(I) 16T10A(I) 20T10A(I)	20T10B(I)	
1200V				25T12H	25T12A(I)	26T12B(I) 41T12B(I)	M40T120A M55T120A
1600V						41T16B(I)	

Trigger Diodes

Silicon Bidirectional Diacs (Glass Seal)

DO-35					
SOD-80					
	PC mW	I _{TRM} A	V _{BO} (V)		
			Min.	Typ.	Max.
DB3	150	2	28	32	36
DC34	150	2	30	34	38
DB4	150	2	35	40	45
DB6	150	16	36	60	70